PERDUE BRANDON

ATTORNEYS AT LAW

OCHILTREE COUNTY SALES MARCH 4, 2025 SCHEDULED FOR 11:00 A.M. OCHILTREE COUNTY COURTHOUSE 511 S MAIN STREET, PERRYTON TEXAS 79070 Tax Sales Information*

- 1) Tax foreclosure sales are conducted by the Sheriff or a Constable of the county where the property is located. These sales are held on the first Tuesday of the month between the hours of 10:00 a.m. and 4:00 p.m. on the courthouse steps at a place designated by the commissioners' court. The Ochiltree County Tax Sale will be held at 11:00 o'clock A.M., on the 4TH DAY OF MARCH 2025, which is the first Tuesday of said month, at the OCHILTREE COUNTY COURTHOUSE, 511 S MAIN STREET of said Ochiltree County, in the City of Perryton Texas.
- 2) All sales are without warranty of any kind. Purchasers receive a Sheriff or Constable's deed that is without warranty. Bidders should satisfy themselves concerning title and location of the property and improvements on the property including any encroachments <u>prior</u> to bidding. Neither our firm nor our clients can guarantee the title to any property. The tax sale is an "as is", "where is", "buyer beware" sale. If you have any questions about specific liens or ownership of the property, you may research the title yourself or through a title company. The judgments in these cases list the parties included in the tax suit.
- 3) Taxes may be due beyond what is listed in the minimum bid amounts and must be paid independently of the bid amount.
- 4) Please contact Maria Brummett at the Perdue, Brandon, Fielder, Collins & Mott, LLP Amarillo Office at 806-359-3188 or the Ochiltree County Appraisal District at 806-435-9623 for further information.

Case No.	Legal Description/Address (if available)	Estimated Minimum Bid	GEO CODE
CV14218 OCHILTREE COUNTY APPRAISAL DISTRICT vs. VELA, EUSEBIO JR	A tract of land 150 feet N-S and 200 feet E-W situated in the south One-half (S/@) of the North One-half (N/2) of Section 3, Block 11, S.F.I.W. Co. Survey, Ochiltree County, Texas, being Tract 2, reserved in favor of the Estates of George W. Powers and Flora Powers, Incompetents, by Percy G. Powers in a Deed to the Dutch Corporation dated May 25, 1966, and recorded in Volume 239, Page 335 of the Deed Records of Ochiltree County, Texas, reference to which Deed is hereby make for all purposes, and which said tract lays immediately West of a .464 acre tract described in said above described Deed as Tract 1, which said Tract 1 was conveyed by G.W. Powers and wife, Flora Powers, and Percy G. Powers, to Louis Melton Orman and wife, Opal Orman, by Deed dated October 22, 1962, and recorded in Volume 199, Page 432, of the Deed Records of Ochiltree County, Texas, and described by metes and bounds therein, said Tract 2 being described by metes and bounds as follows, to-wit: BEGINNING at the SW corner of said Tract 1; THENCE West 200 feet to a point being the SW corner of this Tract 2; THENCE East 200 feet to a point being the NW corner of this Tract 2; THENCE East 200 feet to a point being the NW corner of this Tract 2; THENCE East 200 feet to a point being the NW corner of this Tract 2; THENCE East 200 feet to a point being the NW corner of this Tract 2; THENCE East 200 feet to a point being the NE corner of this Tract 2; THENCE East 200 feet to a point being the NE corner of this Tract 2; THENCE East 200 feet to a point being the NE corner of this Tract 2;	\$25,119.43 SUBJECT TO 2024	560007000000000000

	boundary line of Tract 1 to a point being the POINT OF BEGINNING and the SE corner of this Tract 2 and the SW corner of Said Tract 1		
	ARCH OIL & GAS LLC LSE NAME: LANCE #4 TYPE: REAL LSE NUM :2093 INT TYPE: RI INT %: 0.002273 ACRES: 0 SEC 6 BLK 13 T&NO	\$169.41	0004436-1-0002093
	ARCH OIL & GAS, LLC LSE NAME: LANCE A 1 TYPE: LSE NUM :031383 INT TYPE: RI INT %: 0.00293 ACRES: 0 T&NOSEC 6 BLK 13 FARNSWORTH- CONNER (KANSAS	\$37.00	0004436-1-0031383
CV14308 OCHILTREE COUNTY APPRAISAL DISTRICT vs. GARNER, JUNE LANCE ESTATE	E2 OPERATING LLC LSE NAME: SCHNEIDER C-#2 TYPE: LSE NUM :S0962 INT TYPE: RI INT %: 0.000238 ACRES: 0 AHRENBECK SEC 75 BLK 11 PERRYTON, NW. (MORROW, UPP	\$34.89	0004436-1-0032270
	COURSON OIL & GAS LSE NAME: LANCE #104 TYPE: REAL LSE NUM :32376 INT TYPE: RI INT %: 0.001465 ACRES: 0 SEC 4 BLK 13 T&NO A-924	\$30.00	0004436-1-0032376
	All of Lot Number Thirteen (13), in Block Number Two (2), McGregor Addition to the City of Perryton, Ochiltree County, Texas	\$5,040.72 SUBJECT TO 2024	21002800000000000000
CV15128; PERRYTON INDEPENDENT SCHOOL DISTRICT vs. CHACON, ALBERTO	Lot Number One (1), in Block Number Eight (8), BELMONT ADDITION, an Addition to the City of Perryton, Ochiltree County, Texas, as the same is shown upon the recorded plats of said City and Addition on file in the Office of the County Clerk of Ochiltree County, Texas.	\$11,035.15 SUBJECT TO 2024	030080000000000000000
CV15428 OCHILTREE COUNTY vs. BRAND, PATRICIA ESTATE	BLODGETT ADDITION, Block 1 to the City of Perryton, Ochiltree County, Texas as the same is shown upon the plat of said Addition (ALL OF IT)	\$26,425.01 SUBJECT TO 2024	0400010000000000000
CV15433 OCHILTREE COUNTY vs. MULLINAX, LEONARD ESTATE	All of Lot Number Two (2), in Block Number Six (6), SILVER-DALE ADDITION, an addition to the City of Perryton, Ochiltree County, Texas, as shown upon the recorded plat of said city and addition on file in the office of the county clerk in and for said county and state.	\$7,508.00 SUBJECT TO 2024	38504300000000000000
CV15449 PERRYTON INDEPENDENT SCHOOL DISTRICT vs. JOHNSON ESTATE, THELMA FAYE	LOT 9 BLK 39 OT E 80' OF LOTS 8-9 ORIGINAL TOWN	\$15,942.81 SUBJECT TO 2024	001900100000000000

CV15454 OCHILTREE COUNTY vs. ZEJDA,	Lot Number Six (6), Block Number One (1), Belmont Addition, an Addition to the City of Perryton, Ochiltree County, Texas Lot Number Seven (7), Block Number One (1),	\$11,567.86 \$7,626.04	030006000000000000000000000000000000000
CHRISTINE ESTATE	Belmont Addition, an Addition to the City of Perryton, Ochiltree County, Texas.	ψ1,020.0 4	
		SUBJECT TO 2024	
CV15455 OCHILTREE COUNTY vs. PONDER, DIANE ESTATE	All of Lot Number Three (3), Block Ten (10), Belmont Addition, an Addition to the City of Perryton, Ochiltree County, Texas	\$10,368.72 SUBJECT TO 2024	03009900000000000000
CV14505		50D5L01102024	
PERRYTON INDEPENDENT SCHOOL DISTRICT	LOT THREE (3), IN BLOCK THREE (3), WHEATHEART WEST ADDITION NO. 2 AN ADDITION TO THE CITY OF	\$49,592.23	4660240000000000000
vs. ASHMORE, TERRY	PERRYTON, OCHILTREE COUNTY TEXAS	SUBJECT TO 2024	
CV15135 PERRYTON INDEPENDENT SCHOOL DISTRICT vs.	Lots One (1) and Two (2), Block Fifty-Five (55), FIRST ADDITION to the City of Perryton, Ochiltree County, Texas, as the same are shown upon the plat of said Addition	\$49,090.15	0021110000000000000
SMORE,PROPERTIES, LLC.	recorded in Volume 31, Page 2, Plat Records, Ochiltree County, Texas.	SUBJECT TO 2024	
	Lot Ten (10), Eleven (11), and Twelve (12), Block One (1), Diehl Addition in Ochiltree County, Texas	\$2,972.94	0750050000000000000
CV15390 OCHILTREE COUNTY vs. MUNOZ, ROGELIO & BRISSA	Lot Twelve (12), SAVE AND EXCEPT THE EAST FIVE FEET (E/5'), Block Two (2) LaMaster Addition Unit No. 1, and Addition to the City of Perryton, Ochiltree County, Texas	\$17,799.90	1800260000000000000
MOLINAR	Lot One (1), Block Twenty-four (24), STARK SECOND PARK ADDITION, an Addition to the City of Perryton, Ochiltree County, Texas	\$7,094.19 SUBJECT TO 2024	4020110000000000000
CV15402 OCHILTREE	LOT 11 BLK 1 FULTON	\$2,786.52	1100050000000000000
COUNTY vs. INGRAM, PAULO	LOT 12 BLK 1 FULTON W 102' OF LOT 12	\$3,703.57	1100060000000000000
		SUBJECT TO 2024	
CV15432 OCHILTREE COUNTY vs. MORALES, MIGUEL	LOT 3 BLK 12 SCHOOL	\$1,650.00 SUBJECT TO 2024	3750020000000000000
CV13001A OCHILTREE COUNTY vs. HAWK, SONDRA	A 1,368.05 acre tract of land being a portion of Subdivision & of Johnson and Hoghland Subdivision of the Anthony McGee Headright and a portion of the William Wilmuth Survey, In Ochiltree County, Texas, being further described by metes and bounds as follows: BEGINNING at a fence corner post in the North line of the William Wilmuth Survey,	\$85,317.78 SUBJECT TO 2019-2024	590008000000000000 590008100000000000 59001700000000000000

 whence the Northeast corner of the William Wilmuth Survey and being the Northwest corner of the Anthony McGee Headright, bears S 89°04'39" E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright: THENCE S 89°04'39" E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright: THENCE N 89°581'7" E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°1235" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664"; set '2 1°235" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S N8°0378" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S N8°0378" W, with a fence, a distance of 0221.32 feet to a 1/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 8°0378" W, with a fence, a distance of 076.07 feet to a 1 foot dia. wood fence corner post; THENCE N 8°0378" W, with a fence, a distance of 076.07 feet to a 1 i' ron pipe, found, the Southwest corner of this tract of land; the S00378" W, with a fence, a distance of 6706.07 feet to a 1 i' ron pipe, found, the Southwest corner of this tract of land; theNCE N 1°018" E, with a fence, a distance of 6706.07 feet to a 1 i' ron rol found in the north line of the William Wilnuth Survey; THENCE S 89°0439" E, with a fence, a dista	T		
corner of the Anthony McGee Headright, bears S 89°04'39" E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE 5 89°04'39" E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE N 89°58'17" E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE S 1°12'35" W, a distance of a distance of 427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 47.77 feet to a far effer with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 1°12'133" W, with a fence, a distance of 212.01.5 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 6076.07 feet to a 1 for tod ia.wood fence corner post; THENCE N 1°00'18" E, with a fence, a distance of 676.07 feet to a 1 for tod ia.wood fence corner post; THENCE N 1°00'18" E, with a fence, a distance of 677.7 feet to a 1 'i ron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 6063.79 feet to a 1 'i ron rod found in the north line of the William Willmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a 1 'i ron rod found in the north line of the William Willmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
S 89°04'39' E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE S 89°04'39' E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE N 89°58'17''E, a distance of 803.97 feet to a 3/8'' rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35' W, a distance of 3295.41 feet to a 3/8'' rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33'' E, with a fence, a distance of 1427.54 feet to a 3/8'' rebar with a cap marked "RPLS 4664'', set at a fence corner post; THENCE S 02° 45'48'' E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 90°519' W, with a fence, a distance of 2120.15 feet to a 3/8'' rebar with a cap marked "RPLS 4664'', set at a fence corner post; THENCE S 17°11'33'' W, with a fence, a distance of 177.14 a feat to a 3/8'' rebar with a cap marked "RPLS 4664'', set at a fence corner post; THENCE N 89°45'59'' W, with a fence, a distance of 1164.07 feet to a 1/8'' rebar with a cap marked "RPLS 4664'', set at a fence corner post; THENCE N 89°45'59'' W, with a fence, a distance of 1164.07 feet to a 1 foot dia.wood fence corner post; THENCE N 89°45'59'' W, with a fence, a distance of 6076.07 feet to a 1 foot dia.wood fence corner post; THENCE N 89°45'59'' W, with a fence, a distance of 7978.27 feet to a 1 'i ron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18'' E, with a fence, a distance of 6076.07 feet to a 1'' ron rod found in the north line of the William Willmuth Survey; THENCE S 89°04'39'' E, with a fence, a distance of 6076.37' feet to a 1'' ron rod found in the north line of the William Willmuth Survey; THENCE S 89°04'39'' E, with a fence, a distance of 606.37' Feet to a POINT OF			
Northwest corner of the Anthony McGee Headright; THENCE S 89'04'39' E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE N 89'58'17'E, a distance of 803.97 feet to a 3/8' rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35' W, a distance of 3295.41 feet to a 3/8' rebar with a cap marked "RPLS 4664", set; THENCE N 88'24'33' E, with a fence, a distance of 1427.54 feet to a 3/8' rebar with a cap marked "RPL5 4664', set at a fence corner post; THENCE S 62' 45'48' E, with a fence, a distance of 45.77 feet to a fonce corner post; THENCE S 9'05'19' W, with a fence, a distance of 2120.15 feet to a 3/8' rebar with a cap marked "RPL5 4664", set at a fence corner post; THENCE S 1''11'33' W, with a fence, a distance of 2821.32 feet to a 3/8' rebar with a cap marked "RPL5 4664", set at a fence corner post; THENCE S 10''11'33' W, with a fence, a distance of 607.60'' feet to a 1 foot dia. wood fence corner post; THENCE N 85''45'59' W, with a fence, a distance of 607.60'' feet to a 1 foot dia. wood fence corner post; THENCE N 85''45'59'' W, with a fence, a distance of 7078.27 feet to a 1 foot dia. mood fence corner post; THENCE N 89''03'58' W, with a fence, a distance of 607.60'' feet to a 1'' iron pipe, found, the Southwest corner of this tract of land; THENCE N 1''00'18'' E, with a fence, a distance of 7978.27 feet to a 1'' iron of found in the north line of the William Wilmuth Survey; THENCE S 89''04'39'' E, with a fence, a distance of 606.379 feet to a 1'' iron of found in the north line of the William Wilmuth Survey; THENCE S 89''04'39'' E, with a fence, a distance of 606.379 feet to a 1'' iron of found in the north line of the William Wilmuth Survey; THENCE S 89''04'39'' E, with a fence, a distance of 606.379 feet to a 1''' iron 70F			
Headright; THENCE S 89°04'39" E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE N 89°58'17"E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664'; THENCE S 19'12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664', set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 12821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 164.07 feet to a 1 i ron pipe, found, the Southwest corner of this tract of land; THENCE N 1°0018" E, with a fence, a distance of 7978.27 feet to a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6076.07 feet to a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6076.379 feet to a 10 found found in the north line of the william Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a 10 found found in the north line of the to a 1 found found in the north line of the of the a fence, a distance of 6063.79 feet to a 10 iron rod found in the north line of the of the a fence, a distance of 6063.79 feet to a POINT OF			
THENČE S 89°04'39" E, a distance of 431.92 feet to the Northwest corner of the Anthony McGee Headright; THENCE N 89°58'17"E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 45.77 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 4120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 11°23' W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 8°45'59" W, with a fence, a distance of 607.607 feet to a 1 foot dia. wood fence corner post; THENCE N 1°00'18" E, with a fence, a distance of 607.607 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 607.607 feet to a 1" iron rod found in the north line of the William Wilnuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 607.607 feet to a 1" iron rod found in the north line of the William Wilnuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 607.79 feet to a 1" iron rod found in the north line of the William Wilnuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet		Northwest corner of the Anthony McGee	
feet to the Northwest corner of the Anthony McGee Headright; THENCE N 89°581'7"E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 4.5.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1 'iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 6076.07 feet to a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a 1 foor dia.			
McGee Headright; THENCE N 89°5817"E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 427.75 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 6076.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet to a 1" iron rol found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE S 89°04'39" E, with a fence, a distance of 607.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE S 89°04'39" E, with a fence, a distance of 607.07 feet to a 1" iron pipe, found, the southwest corner of this tract of land; THENCE S 89°04'39" E, with a fence, a distance of 607.07 feet to a 1" iron pipe, found, in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 607.37 feet to a 2" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a ADINT OF			
THENCE N 89°58'17"E, a distance of 803.97 feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°3'58' W, with a fence, a distance of 607.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet to a 1" iron prop,		feet to the Northwest corner of the Anthony	
feet to a 3/8" rebar with a cap marked "RPLS 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 281.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6067.07 feet to a 1° iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet to a 1° iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
 4664"; THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88"24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 6076.07 feet to a 1 " iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet to a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°0'39" E, with a fence, a distance of 7978.27 feet to a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°0'39" E, with a fence, a distance of 6063.79 feet to a POINT OF 			
THENCE S 1°12'35" W, a distance of 3295.41 feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF<			
feet to a 3/8" rebar with a cap marked "RPLS 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
 4664", set; THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°0'3'8" W, with a fence, a distance of 6076.07 feet to a 1 "iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 8°04'39" E, with a fence, a distance of 607.79 feet to a POINT OF 		THENCE S 1°12'35" W, a distance of 3295.41	
THENCE N 88°24'33" E, with a fence, a distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1 foot dia. wood fence corner post; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		feet to a 3/8" rebar with a cap marked "RPLS	
distance of 1427.54 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
cap marked "RPLS 4664", set at a fence corner post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1 " iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
post; THENCE S 62° 45'48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 1427.54 feet to a 3/8" rebar with a	
THENCE S 62° 45′48" E, with a fence, a distance of 45.77 feet to a fence corner post; THENCE S 9°05′19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11′33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45′59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03′58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00′18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04′39" E, with a fence, a distance of 6063.79 feet to a POINT OF		cap marked "RPLS 4664", set at a fence corner	
distance of 45.77 feet to a fence corner post; THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
THENCE S 9°05'19" W, with a fence, a distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
distance of 2120.15 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664",set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 45.77 feet to a fence corner post;	
cap marked "RPLS 4664", set at a fence corner post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664",set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
post; THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664",set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 2120.15 feet to a 3/8" rebar with a	
THENCE S 17°11'33" W, with a fence, a distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664", set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		cap marked "RPLS 4664", set at a fence corner	
distance of 2821.32 feet to a 3/8" rebar with a cap marked "RPLS 4664",set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		post;	
cap marked "RPLS 4664",set at a fence corner post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		THENCE S 17°11'33" W, with a fence, a	
post; THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 2821.32 feet to a 3/8" rebar with a	
THENCE N 85°45'59" W, with a fence, a distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		cap marked "RPLS 4664", set at a fence corner	
distance of 1164.07 feet to a 1 foot dia. wood fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		post;	
fence corner post; THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		THENCE N 85°45'59" W, with a fence, a	
THENCE N 89°03'58' W, with a fence, a distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 1164.07 feet to a 1 foot dia. wood	
distance of 6076.07 feet to a 1" iron pipe, found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
found, the Southwest corner of this tract of land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		THENCE N 89°03'58' W, with a fence, a	
land; THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 6076.07 feet to a 1" iron pipe,	
THENCE N 1°00'18" E, with a fence, a distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey;THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		found, the Southwest corner of this tract of	
distance of 7978.27 feet t o a 1" iron rod found in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		land;	
in the north line of the William Wilmuth Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF			
Survey; THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		distance of 7978.27 feet t o a 1" iron rod found	
THENCE S 89°04'39" E, with a fence, a distance of 6063.79 feet to a POINT OF		in the north line of the William Wilmuth	
distance of 6063.79 feet to a POINT OF		Survey;	
		THENCE S 89°04'39" E, with a fence, a	
BEGINNING.		distance of 6063.79 feet to a POINT OF	
		BEGINNING.	

This notice and the materials provided herein are for informational purposes only and do not constitute any legal advice. No reader should rely on, act, or refrain from acting on the basis of any information contained in this notice without seeking their own legal or other professional advice. Perdue, Brandon, Fielder, Collins, & Mott. L.L.P. ("PBFCM") <u>DOES NOT</u> <u>WARRANT</u> the quality or completeness of the information provided herein. The information in this notice is not intended to nor does it create any attorney-client relationship between the reader and PBFCM